

KK-300A / LB / W | Animal Bench Scale



TOTAL WEIGHING SOLUTION™

KENKO®
Panasonic Kenko Electric. Co.Ltd



...Clearly a Better Value

KK-300A

- Accurate to Within 1/2 lb
- Dual Slide-Out Gates Included
- Stainless Steel Junction Box
- Stainless Steel Load Cells
- Up to 5,000 lb Capacity



Certificate of Conformance
No. 13-083



Indicator sold separately

NEW! LB SERIES LOAD BARS FARM WEIGHING APPLICATIONS

KK-300LB



Versatile Weighing:
Alleyway Platforms,
Cages, Squeeze Chutes,
Bins, and Hoppers

KENKO®

Warranty - Two Years

KK-300W





Model Capacity Size Loadcell

<u>KK-300A</u>	<u>2 Ton</u>	<u>2 x 1 meter</u>	<u>4 Pcs</u>
<u>KK-300LB</u>	<u>2 Ton</u>	<u>100 x 1000 mm</u>	<u>4 Pcs</u>
<u>KK-300W</u>	<u>100 kg</u>	<u>50 x 40 cm</u>	<u>1 Pcs</u>

Digital Display

Technical Parameter

Grad	: 1/3000, 1/6000, 1/7500
Input signal	: 10 mV
Converting speed	: 40 times/second
A/D code	: 360000
Non-linearity	: 0.03%
Drift	: 0.03%
Stimulating voltage	: DC +5V
Display	: 0 - 999999
Interval	: 1/2/5/10/20/50
Peak holding function	
Serial communication interface	RS232C
Power supply	: AC 180V - 240V 49 - 51Hz
Ambient temperature	: 0 - 40 °C
Humidity	: 85 RH
Fuse	: 500 mA
Dimensi Display/indicator	: 25x17x15cm
Tiang penyangga	: besi bulat chrome tinggi 80-100cm
Material	: mild steel

Platform

Dimensi	: (200-203) x (70-72) x (10-12) cm
Material	: wood & steel
Kayu	: Kalimantan / Bangkirai tebal 3cm
Rangka	: Mild steel holo (50-52) x (50-52) x (2-3) mm
Permukaan	: tidak licin (dilapisi karet sapi)
Dudukan load beam	: Mild steel UNP 8, tebal (3-4) mm
Finishing	: coating primer

Technical parameter

Rated load	: 0.5 t
Sensitivity	: $3.0 \pm 0.1\%$ mV/V
Total error	: $\pm 0.02\%$ F.S
Creep (30min)	: $\pm 0.03\%$ F.S
Zero balance	: $\pm 1\%$ F.S
TCO	: $\pm 0.02\%$ F.S/10°C
TC SPAN	: $\pm 0.02\%$ F.S/10°C
Input resistance	: $400 \pm 10\Omega$
Output resistance	: $352 \pm 2\Omega$
Operating temp range	: -30 - +70 °C
Safe load limit	: 150% F.S
Lateral load limit	: 250% F.S
Recommend excitation	: 10 -12V DC
Maximum excitation	: 15V DC
Protection class	: IP 68
Construction	: Alloy Steel
Cable	: length : 4m
Diameter	: 5mm



...Clearly a Better Value

Specifications subject to change without notice



Panasonic Kenko Electric Co, Ltd

36 Sisenju, Okio, Osaka 234-23354 Japan

Tel. 81-32-565434667

Specifications subject to change without notice